



Certificate of Constancy of Performance

Koroseal Interior Products

3875 Embassy Parkway – Fairlawn, OH 44333

Trading As: **Korographics**

In compliance with Regulation 305/2011/EU of the European Parliament and the Council of 9 March 2011 (The Construction Products Regulation or CPR), we do hereby declare that the CE marked products specified in Table 1 conform to the product performance requirements of annex ZA in the product standard:

EN 15102:2007 +A1:2011

Decorative Wallcoverings - Roll and Panel Form

Table 1

Construction Product Description:	Classification Report:	Reaction to Fire:		
Fabric and Nonwoven backed vinyl wallcovering: 271 gm/m ² to 339 gm/m ²	WFRGENT Reaction to fire classification Nr 13171C	B s2 d0		
Fabric and Nonwoven Backed vinyl wallcovering 651 gm/m ² – 744 gm/m ²	WFRGENT Reaction to fire classification Nr 138393C	B s2 d0		
Fabric and Nonwoven Backed TPO wallcovering (Option e) 383 gm/m ²	WFRGENT Reaction to fire classification Nr 14262E	B s2 d0		
Other requirements:	Release of Heavy metals and specific elements -	Pass		
Release of Formaldehyde – (< 120mg/Kg)	Heavy Metal	Specification	Vinyl	TPO
	Antimony	No upper limit	1	2.3
Release of Vinyl Chloride Monomer – Pass (< 0.2mg/Kg)	Arsenic	< 25 mg/Kg	< 2	<2
	Barium	< 500 mg/Kg	< 2	38
	Cadmium	< 25 mg/Kg	< 0.2	<0.2
	Chromium	< 60 mg/Kg	< 1	<1
	Mercury	< 20 mg/Kg	< 0.05	<0.05
	Lead	< 90 mg/Kg	< 2	<2
Sound Absorption – No performance determined	Selenium	< 165 mg/Kg	< 2	<2
	Test Report: T V Rheiland Report: 9904R-10.28608			
Thermal Resistance – No performance determined				
Intended Use: Hanging on to internal walls, or partitions, by means of adhesive for the primary purpose of decoration.				
Notified Certification Body: Laboratoire national de métrologie et d'essais Paris, France 75724				
EC Reference Number: 0459		Manufacturing Site Reference:		
0071-CPD-20376				

Signed:
Name: Wally Yocum

Position: Technical Manager
Date: January 28, 2014